
Mechanical Part
Backlight Circuit Diagram
SHANTOU GOWORLD DISPLAY CO., LTD.


Mechanical Part
Backlight Circuit Diagram
SHANTOU GOWORLD DISPLAY CO., LTD.


Block Diagram
BACKLIGHT
TFT LCD PANEL
LCD Driver
TOUCH PANEL
FPC
DISPLAY TYPE: a-si TFT(TFT mode) / 16.7M Colors
DISPLAY MODE: Transmissive / Normally Black
VIEWING DIRECTION: 12:00
LCD BL SUPPLY MIN.77(typ. value, Vled Edet Vrdt.)
VDD=1.8V, AVDD=11V, VGH=30V, VGL=-7.5V
VCOM=3.1V, Intensity gamma=2.2
CTP SUPPLY INPUT: TP_VDD=3.3V (TYP.)
IOVDD=1.8V, Intensity gamma=2.2
LCD INTERFACE : MCU Interface
TOUCH INTERFACE: I2C
BACKLIGHT: White LED (8 pcs in series, 7 branches)
LCM LUMINANCE: 350cd/m2(typ. @ IF=40mA)
OPERATING TEMPERATURE: -20°C ~ +70°C
STORAGE TEMPERATURE: -30°C ~ +70°C
NOTE: WITH "√" PLEASE CHECK
SHANTOU GOWORLD DISPLAY CO., LTD.


Front View
Back View
Note:
IC: ST1633I
VDD=3.3V±0.1V, IOVDD=1.8V±0.1V
Operating temp.: -20° ~ +60° C
Storage temp.: -30° ~ +70° C
Lens material: Dragon Trail glass
Dimensions with ○ are for reference
Dimensions with ⊕ are pivotal
General tolerance: ±0.30mm
SHANTOU GOWORLD DISPLAY CO., LTD.